



The Right Product, For the Right Application

**Trinity Natural Gas Engine Oils are formulated to deliver RESULTS.
Lowering your Operating Costs and overall “Cost of Ownership”**

Our “Good / Better / Best” family of NGE0 Low Ash engine / compressor oils deliver consistent performance you can count on.

“Good”

Trinity Premium has been protecting engines for over 12 years, and consistently provides protection against Premature Valve Recession / Top End Deposits / Extended Oil Drains (750 to 1500 hours depending on GAS make-up)

“Better”

Trinity Performance adds extended Oil drain intervals Extends top end overhauls closer to OEM recommendation and supported with our Oil Analysis Program sampling every 30 days, Access Historical Data 24/7 (1500 to 3000 hours depending on GAS make-up)

“BEST”

Trinity Performance Plus lower's cost of ownership in SEVERE applications such as: Transmission of Sour Gas and Landfill operations Extended Oil drain intervals beyond 3000 hours depending on LABORATORY RESULTS of our: Oil Condition Monitoring program sampling every 30 days, Access Historical Data 24/7

SAE		Trinity NGE0 Premium 40w Low Ash	Trinity NGE0 Performance 40w Low Ash	Trinity NGE0 Performance Plus 40w Low Ash
D445	Viscosity @ 40°C	127.6	129.4	130.5
	Viscosity @ 100°C	13.5	13.9	13.9
D 2270	Viscosity Index, Min.	101	107	103
D 92	Flash Point, °F	460	485	490
D 97	Pour Point, °F	-20	-20	-18
D 874	Sulfated Ash, % Mass	.5	.5	.5
D 2896	Total Base No, min.	5.1	5.5	6
XRF	Calcium % wt	0.123	0.122	0.122
	Zinc %wt	0.034	0.030	0.032
	Phosphorus % wt	0.031	0.029	0.030
D 892	Foam Test, Volume Foam / mL Sequence I, II, III	Pass	Pass	Pass
OEM(s)	Documented Successful Field Trials completed in the following engines. Meets or Exceeds OEM specifications	Caterpillar Waukesha	Caterpillar Waukesha Jenbacher	Caterpillar Waukesha Jenbacher

832-499-2821

27663 Concho Dr, Splendora, Tx 77372 USA

INFO@360COMPSERV.COM

WWW.360COMPSERV.COM