



NATIONAL™ FULL SYNTHETIC MULTI-VEHICLE ATF | Transmission & Drive Train

Product Description

NATIONAL FULL SYNTHETIC MULTI-VEHICLE ATF offers extended friction control protection that lasts over the life of the fluid—long after the anti-shudder protection found in many competitive brands. Made with full synthetic base stocks, this high viscosity Multivehicle ATF is inherently more thermally stable when compared with conventional base stocks.

NATIONAL FULL SYNTHETIC MULTI-VEHICLE ATF is designed for use in most modern passenger vehicles and heavy duty applications. It also can be used in applications where its performance features exceed the requirements of older specifications.

Features

- Full synthetic formula with outstanding low temperature performance
- Improved wear performance and reduced oil consumption
- Provides extended anti-shudder performance for smooth driving
- Excellent oxidation and thermal stability
- Exceeds the most demanding JASO 1A performance standard

Technical Data (typical values)

	ASTM	Typical
Product Number	07-001080	
SDS Number	S008	
Viscosity @ 100°C, cSt	D445	6.9
Viscosity @ 40°C, cSt	D445	36.26
Viscosity Index	D2270	153
API Gravity	Calc.	34.2
Pour Point, °C	D5950	-54
Brookfield @ -40°C, cP	D2983	19,000
Color ASTM	Visual	Red

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

