



MAJESTIC UNIVERSAL TRACTOR | Hydraulic Fluid

Product Description

MAJESTIC UTHF is formulated with high quality base stocks, a shear stable viscosity index improver, oxidation and corrosion inhibitors, antifoaming agents, antiwear additives, and a pour point depressant to exceed the performance and protection requirements of most tractors and other farm equipment used in North America¹.

Industry and OEM Specifications

- JDM J20C and J20A²
- API GL-4³
- Allison C-2, C-3 and C-4⁴

Applications

MAJESTIC UTHF is a multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

Features

- Excellent anti-wear capabilities
- EP & Load carrying capabilities
- One fluid does the job of a full range of tractor hydraulic systems
- Good compatibility with seals, O-rings, and packing materials maintains their good condition and keeps leakage at a minimum
- Friction durability
- Oxidation and thermal stability
- Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods
- Formulated to suppress brake “chatter” and transmission “slip” for quiet and efficient action of brakes and transmission

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Technical Data

(typical values)

MAJESTIC UNIVERSAL TRACTOR		
Product Number	07-392700	
SDS Number	S100	
Viscosity @ 100°C, cSt	D445	9.8
Viscosity @ 40°C, cSt	D445	65.62
Viscosity Index	D2770	132
Specific Gravity @ 60°F	D405	0.8692
	2	
Pour Point, °C	D5950	-42
Brookfield @ -35°C, cP	D2983	37,000
Color ASTM	D1500	2

- 1) Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices
- 2) Obsolete
- 3) API GL-4 is an automotive gear lubricant specification and this product is not recommended for use in hypoid applications
- 4) Allison no longer recommends THF in their transmissions

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

