



NATIONAL™ POWER STEERING HVI | Specialty Oils and Fluids

Product Description

NATIONAL POWER STEERING FLUID HVI contains a unique additive system designed to provide protection against wear, corrosion and rust. It reduces power steering noise (squeal), conditions seals and gives protection against pump wear.

Industry and OEM¹ Specifications

- Chrysler MS-5931
- Ford ESW-M2C128-C or D
- GM 9985010
- AMC 4124

Applications

NATIONAL POWER STEERING FLUID HVI can be used in most domestic and imported power steering systems in automobiles and light trucks. It is also suitable for power steering applications where automatic transmission fluids are specified. It is not recommended for use in Honda vehicles.

Features

- Excellent Rust and Oxidation protection
- Keeps seals & O-rings pliable
- Helps to prevent leakage
- Reduces squealing under severe conditions
- Will not clog or foam, maintains performance
- For year-round use

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Technical Data

(typical values)

Description	ASTM	Typical
Product Number		07-706241
SDS Number		S139
Viscosity @ 100°C, cSt	D445	7.82
Viscosity @ 40°C, cSt	D445	40.26
Viscosity Index	D2270	169
Specific Gravity at 60°F	D4052	0.8527
Pour Point, °C	D5950	-54
Color ASTM	D1500	L0.5
Brookfield @ -40°C, cP	D2983	20,000

1. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and maintenance practices.
2. Not recommended for use in Honda power steering units

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

